Material and Finish Codes

Z1 - CS, HD Galvanized, Chem Treated G90 Z2 - CS, .0002 min Zinc, Clear


Cushion is Black Vinyl, 1/32" Thick


bb = 09

aa + 12

32

REVISIONS						
REV.	DESCRIPTION	DATE	APPROVED			
1	Corrected Center to Center Formulas	5/2/2022	C. Goettl			
2 Material Thickness Change		6/27/2023	C. Goettl			
	•					







As Supplied (Open Position)

circular hole with diameter H on the top side and a slotted hole with H width, and length S, on the bottom side.

	bb	Hole Diameter (H)	Hole Center to End (E)	Slot Length to End (F)	Slot Length (S)	Width (W)	Material Thickness (T)
	09	.281	.250	.296	.375	.500	
D	11	.343	.281	.328	.437	.562	.032
В	13	.406	.312	.359	.500	.625	
		± .005	± .015	± .015	± .020	± .010	

32

Center to Center


(L)

bb = 11


aa + 13

32

±.031



EXPLANATION OF PART CALLOUT



EXAMPLE OF PART CALLOUT

<u>CFV - 12 13 Z1</u>

This part number indicates the clamp will have dimensions: Clampina Diameter (D) = .750 Hole Diameter (H) = .406Center to Center (L) = .843 Width (W) = .625Hole Center to End (E) = .312 Slot Center to End (F) = .359Slot Length (S) = .500

Made from Hot Dipped Galvanized Steel Cushion is Black Vinyl, 1/32" Thick



THE ORIGINAL CLIP & CLAMP CO. **1221 SOUTH PARK STREET**

PORT WASHINGTON, WI 53074 (262) 377-5030

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KICKHAEFER MANUFACTURING COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KICKHAEFER MANUFACTURING COMPANY IS PROHIBITED.

PART SERIES MASTER PRINT

CFV

COATED, FLARED EDGE **CLAMPS**

DRAWN	CHECKED			
ВС	KW			
8/22/17	9/11/18			
NOT TO SCALE				

5

Clamping Diameter

(D)

aa - 1

16

 $\pm .031$